



PORTABLE FIRE EXTINGUISHERS

Portable Fire Extinguishers are used for putting out or containing small fire until fire department arrives. ACCUREX Portable Fire Extinguisher comply to KM EN – 3, they are light weight and easy to use, suitable for industrial, commercial and home use.

Accurex Fire Systems B.V.


Kingsfordweg 151, 1043GR Amsterdam, The Netherlands
www.accurexfiresystems.com, info@accurexfiresystems.com

Kitemark Approved, Pressure Type

Dry Chemical Powder Fire Extinguishers are the most widely used type of fire extinguisher. They discharge a fine powder that absorbs fuel molecules, depriving the fire of a fuel source.

Features

- Easy grip control valve
- Refillable and parts are replaceable
- Comes with heavy-duty bracket
- High Quality Polyester paint.
- Choice of capacity for 1kg, 2 kg, 6 kg and 9kg.



| MODEL | MFZL 1 | MFZL 2 | MFZL 6 | MFZL 9 |
|---|-----------------------------|-----------|------------|------------|
| Fire Class | ABC | | | |
| Extinguishing Agent | 40% ABC Dry Chemical Powder | | | |
| Capacity | 1kg | 2kg | 6kg | 9kg |
| Propellant | Nitrogen | | | |
| Fire Rating (BS EN 3-7:2004+A1:2007) | 8A 34B C | 13A 55B C | 43A 233B C | 55A 233B C |
| Discharge Duration | 6s | 9s | 15s | 18s |
| Operating Temperature Range | -20°C to 60°C | | | |
| Working Pressure | 18bar | | | |
| Test Pressure | 29bar | | | |
| Extinguisher Weight | 2kg | 3.7kg | 9.5kg | 13.7kg |
| Total Height | 280mm | 315mm | 445mm | 510mm |
| Cylinder Diameter | 85mm | 110mm | 160mm | 180mm |
| Cylinder Material | Steel | | | |
| Body Color | RAL 3000 (Signal Red) | | | |
| Certification | Kitemark EN3 | | | |

SPECIFICATION

Kitemark Approved

Carbon Dioxide Fire Extinguishers are designed to protect areas where class B and electrical fire occur. Carbon Dioxide extinguishers are used indoors where winds and drafts do not affect discharge and where clean agent is required.

Features

- Easy grip control valve
- Seamless, corrosion-resistant body
- Refillable and parts are replaceable
- Comes with heavy-duty bracket
- Choice of capacity for 2 kg and 5 kg.



| MODEL | MT-2 | MT-5 |
|---|-----------------------|---------------|
| Fire Class | BE | |
| Extinguishing Agent | Carbon Dioxide | |
| Capacity | 2kg | 5kg |
| Propellant | Carbon Dioxide | |
| Fire Rating (BS EN 3-7:2004+A1:2007) | 34B | 89B |
| Discharge Time | 10s | 15s |
| Operating Temperature Range | -30°C ~+ 60°C | -20°C ~+ 60°C |
| Working Pressure | 174bar | |
| Test Pressure | 250bar | |
| Extinguisher Weight | 4.7kg | 6.3kg |
| Total Height | 385 ± 5mm | 655 ± 5mm |
| Cylinder Diameter | 116mm | 136mm |
| Cylinder Material | 34Cr MO 4 | |
| Body Color | RAL 3000 (Signal Red) | |
| Certification | Kitemark EN-3 | |

SPECIFICATION

Kitemark Approved

Water Extinguishers are very effective against fire in furniture, fabrics, as well as deep-seated fire because it cools down the burning materials by absorbing the heat.

Features

- Easy grip control valve
- Seamless, corrosion-resistant body
- Refillable and parts are replaceable
- Comes with heavy-duty bracket
- Choice of capacity for 6 L and 9 L



| MODEL | MSQ 6 | MSQ 9 |
|---|-----------------------|---------------|
| Fire Class | A | |
| Extinguishing Agent | Water | |
| Capacity | 6 L | 9 L |
| Propellant | Nitrogen | |
| Fire Rating (BS EN 3-7:2004+A1:2007) | 21A | 27A |
| Discharge Time | 35s | 45s |
| Operating Temperature Range | +5°C ~+ 60°C | -20°C ~+ 60°C |
| Max Working Pressure | 18bar | |
| Test Pressure | 29bar | |
| Extinguisher Weight | 9.3kg | 13.7kg |
| Total Height | 445 ± 5mm | 510 ± 5mm |
| Cylinder Diameter | 160mm | 180mm |
| Cylinder Material | SPACE | |
| Body Color | RAL 3000 (Signal Red) | |
| Certification | Kitemark EN-3 | |

SPECIFICATION

Kitemark Approved

Aqueous Film-Forming Foam (AFFF) Extinguishers can be used on class A and B fire and for vapor suppression. This is because the foam blankets the fuel preventing oxygen from reaching it.

Features

- Easy grip control valve
- Seamless, corrosion-resistant body
- Refillable and parts are replaceable
- Comes with heavy-duty bracket
- Choice of capacity for 6 L and 9 L



| MODEL | AFF 6 | AFF 9 |
|---|-----------------------|------------|
| Fire Class | AB | |
| Extinguishing Agent | Foam (3% FFF) | |
| Capacity | 6 L | 9 L |
| Propellant | Nitrogen | |
| Fire Rating (BS EN 3-7:2004+A1:2007) | 21A 144 BC | 27A 183 BC |
| Discharge Time | 54s | 76s |
| Operating Temperature Range | +5°C ~+ 60°C | |
| Max Working Pressure | 18bar | |
| Test Pressure | 29bar | |
| Extinguisher Weight | 9.3kg | 13.7kg |
| Total Height | 445 ± 5mm | 510 ± 5mm |
| Cylinder Diameter | 160mm | 180mm |
| Cylinder Material | SPACE | |
| Body Color | RAL 3000 (Signal Red) | |
| Certification | Kitemark EN-3 | |

SPECIFICATION